

Centrifugal pumps



MODEL		*	POWER		PERFORMANCE		PORTS	
single-phase	three-phase		kW	HP	Q l/min	H meters	suct.	deliv.
CPm 100	–	1	0.25	0.33	10 ÷ 60	15 ÷ 7	1"	1"
CPm 130	CP 130 ²		0.37	0.50	10 ÷ 80	22 ÷ 14		
CPm 132A	CP 132A		0.60	0.85	20 ÷ 120	22 ÷ 9		
CPm 150	CP 150		0.75	1	20 ÷ 120	29 ÷ 15		
CPm 158	CP 158 ³		0.75	1	10 ÷ 90	34 ÷ 25		
CPm 170	CP 170	1	1.1	1.5	30 ÷ 120	38 ÷ 22	1 1/4"	1"
CPm 170M	CP 170M		1.1	1.5	30 ÷ 160	35 ÷ 19		
CPm 190	CP 190		1.5	2	30 ÷ 140	46 ÷ 26		
–	CP 200		2.2	3	30 ÷ 140	55 ÷ 38		
CPm 160C	CP 160C	2	1.1	1.5	50 ÷ 200	31 ÷ 20	1 1/2"	1"
CPm 160B	CP 160B		1.5	2	50 ÷ 220	36 ÷ 23		
–	CP 160A		2.2	3	50 ÷ 240	42 ÷ 26		
CPm 210C	CP 210C		2.2	3	50 ÷ 250	45.5 ÷ 27		
–	CP 210B		3	4	50 ÷ 270	53 ÷ 34		
–	CP 210A	4	5.5	50 ÷ 280	61 ÷ 40			
CPm 220C	CP 220C	2	2.2	3	50 ÷ 450	31.5 ÷ 21	2"	2"
–	CP 220B		3	4	50 ÷ 450	37.5 ÷ 25		
–	CP 220A		4	5.5	50 ÷ 450	48.5 ÷ 36		
–	CP 220AH		5.5	7.5	50 ÷ 450	51.5 ÷ 42		
–	CP 230C		3	4	100 ÷ 850	29.5 ÷ 9		
–	CP 230B		4	5.5	100 ÷ 900	38.5 ÷ 13		
–	CP 230A		5.5	7.5	100 ÷ 900	45.5 ÷ 15		
–	CP 250C		7.5	10	100 ÷ 900	56 ÷ 24		
–	CP 250A	11	15	100 ÷ 900	73 ÷ 37			

- Pump body: cast iron
- * Impeller: 1=AISI 304 stainless steel; 2=brass; 3=cast iron
- Protection: IP X5 for CP 220, CP 230, CP 250
- Registered Community Design n° 002098434 per CP 100÷210
- Registered Italian Design n° 72753 per CP 220÷250

• Registered trade mark